

STANDARD FEATURES

- To Latest Specification MIL 1-17244E (Ships)
- Vibration Resistant to MIL STD 167D
- Shock Resistant to MIL S-901C
- All Stainless Steel Construction
- External Recalibration Adjustment
- Dished Anti-Parallax Dial
- Accurate to $\pm 1\%$ of Scale Range
- All Models Listed Below Have Been Approved by NAVSEA
- $\frac{3}{4}$ "-28 UN2A Union Connection Assembly Must be used with Well (or Bushing)

CATALOG NUMBER	NATIONAL STOCK NUMBER (NSN)	STEM LENGTH	RANGE °F	FORM
E318A2	6685-00-782-5244	2"	-40/180	Back
E31802	6685-00-782-5230	2"	-40/180	Bottom
E318A4	6685-00-782-5231	4"	-40/180	Back
E31804	6685-00-782-5232	4"	-40/180	Bottom
E318A4R3*	6685-00-239-6679	4"	-40/180	Back
E324A2	6685-00-782-5249	2"	20/240	Back
E32402	6685-00-782-5247	2"	20/240	Bottom
E324A4	6685-00-782-5236	4"	20/240	Back
E32404	6685-00-782-5234	4"	20/240	Bottom
E324A4R3*	6685-00-404-3715	4"	20/240	Back
E355A4	6685-00-841-1439	4"	50/550	Back
E35504	6685-00-066-6102	4"	50/550	Bottom

*THESE CATALOG NUMBERS (WITH "R3" AT END) ARE NAVY TYPE "ITM" WITH BOTH MAXIMUM AND MINIMUM INDICATING HANDS

